



MOHINDRA FASTENERS LIMITED





POWERING THE PRODUCTION OF TOMORROW

FASTENING SOLUTIONS FOR AUTOMOTIVE, RAILWAYS AND INDUSTRIAL APPLICATIONS

Corporate Office: 304, Gupta Arcade, Inder Enclave, Rohtak Road, New Delhi-110087, INDIA
T : +91 11 46200400, 46200401, E : fasteners@mohindra.asia



Standard Product Range

DRAWING	DESCRIPTION	INTERNATIONAL STANDARDS		GRADE	SIZE	
		DIN / ISO / IS	ANSI / ASME		MIN. DIA.	MAX. DIA.
	Hexagon socket countersunk head cap screws	DIN 7991 ISO 10642	B18.3	08.8 010.9	M3 #10	M24 1"
	Hexagon socket button head screws	ISO 7380-1	B18.3	010.9	M3 #10	M16 5/8"
	Hexagon socket button head screws with collar	ISO 7380-2	--	010.9	M4	M12
	Hexagon socket head cap screws H/T	DIN 912* ISO 4762	B18.3	12.9	M6 1/4"	M48 1"
	Hexagon socket head cap screw with a low profile head	DIN 7984	--	08.8 010.9	M5	M20
	Low socket cap screw with Pilot Hole	DIN 6912	--	08.8 010.9	M5	M20
	Pass-shoulder screws with hexagon socket	ISO 7379	B18.3	012.9 A2 / 18-8	Ø5 Ø3/16"	Ø24 Ø1"
	Hexalobular socket Head Cap Screws	ISO 14579	--	8.8	M4	M10
	Hexalobular socket Cheese Head Screws	ISO 14580	--	08.8	M5	M10
	Hexalobular socket countersunk flat head screws	ISO 14581	--	08.8	M4	M10
	Button head screws with Hexalobular socket	DIN 34805-1	--	010.9	M4	M10
	Button head screws with Hexalobular socket with flange	DIN 34805-2	--	010.9	M4	M10
	Hexagon socket pipe plugs, conical threads	DIN 906	B.1.20.3 Dry & Flush seal	Steel Stainless Steel Brass	M10 R1/8"	M60 R1.1/2"
	Hexagon socket screw plugs, cylindrical threads	DIN 908	--	Steel Stainless Steel Brass	M10 G1/8"	M64 G2"
	Hexagon head screw plugs, cylindrical threads	DIN 910	--	Steel Stainless Steel Brass	M10 G1/8"	M64 G2"
	Hexagon head screw plugs, cylindrical threads	DIN 7604	--	Steel Stainless Steel Brass	M8	M52
	Hexagon head screw plugs, cylindrical threads	DIN 5586	--	Steel Stainless Steel	G1/8"	G2"
	Dowel pins (Hardened and ground)	DIN 6325 ISO 8734	B18.8.2	Steel	Ø2 Ø1/8"	Ø20 Ø1"
	Dowel pins (Unhardened and ground)	DIN 7 ISO 2338	--	Steel Stainless Steel	Ø2	Ø50
	Taper Dowel pins	DIN 1	--	Steel	Ø2	Ø50
	Parallel Pins with internal threads	DIN 7979 ISO 8735	--	Steel	Ø4	Ø50
	Taper Pull Dowel pins	DIN 7978	--	Steel	Ø6	Ø50

* DIN 912-We offer only long lengths upto M24 and full range in hot forging from M30 to M48.

● Length depending upon the product and Diameter.

● We offer the above range in following surface finishes-Self colour, Phosphated, Zinc Passivated, Zinc Flake ,Zinc Nickel, Zinc Iron ,Xylan Plating and Ultrasonic cleaning.